



Product Service

CERTIFICATE

No. Z2 017297 0514 Rev. 00

Model(s): 4591-70-K-X, 4591-71-X, 4591-71-1-X, 4591-72-X,
4591-80-X, 4591-81, 4951-X, 4591-81AM,
4591-81BM, 4591-81-RM, 4591-81GM

Parameter:

Art.-No. / Name	l x w x h [m]
4591-70-K-X Slackmaster	3.10 x 3.50 x 2.04
4591-71-X Slackmaster-combination 1 double version	4.00 x 4.00 x 1.44
4591-71-1-X Slackmaster-combination 1 basic version	5.40 x 0.50 x 1.44
4591-72-X Slackmaster-combination 2	3.50 x 3.50 x 2.44
4591-80-X Slack Bar	5.30 x 0.10 x 0.35
4951-X Gummi-Jumper	8.10 x 1.40 x 0.70
4591-81 Balancing snacke	9.40 x 0.16 x 0.60
4591-81AM Anaconda Maxi	5.45 x 5.50 x 0.60
4591-81BM Blindworm Midi	4.15 x 4.13 x 0.60
4591-81RM Earthworm Mini	3.16 x 3.67 x 0.60
4591-81GM Green Mamba	3.50 x 2.33 x 0.60

The X stands for the following variations of the posts:

S - Steel, St37-2, hot-dip galvanized

PS - Douglas fir incl. hot-dip galvanized post shoe

R - Robinia, as grown, splint free

Post: Steel Ø102 mm, Douglas fir Ø160, 180, 200 mm

Robinia Ø160 - 400 mm

Ropes/nets: in Hercules quality
with steel core, Ø16 mm

Tested according to: DIN EN 1176-1:2017
EN 1176-1:2017

Production Facility(ies): 017297

TUV SUD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT